



LED Fixture w Bracket




9-LED FIXTURE


PROJECT:
TYPE:
ORDERING # :
COMMENTS:

FEATURES


- Aluminum, Brass, & Copper Plated Housings w/ Multiple Finish Options
- Stainless Steel Mount Brackets
- Stainless Steel Mounting Screws
- 9-15V AC/DC Operating Range w/ Integrated, Constant Voltage Driver
- 10-Year / 40,000 Hour Warranty on LED Driver & All Other Electrical Components
- Available in 3, 6, & 9 LED Configurations
- Casts a Low, Even Spread of Energy Efficient LED Light
- 2950K (-150 / +175) High CRI
- 70" of Useable #18-2, SPT-1W Leads. Cable Connector Supplied. WHT Finished Fixtures Have Coordinating White Leads
- 5-Year Warranty on Aluminum LED Housings & Exterior Finishes



3 LED		Distance from Light Source					
Mounting Height	0'	1'	2'	3'	4'		
foot candles at 12"	38.00	4.3	1.60	0.82	0.50		
foot candles at 24"	8.71	4.40	1.08	0.64	0.43		
foot candles at 36"	4.00	2.39	1.45	0.52	0.32		



6 LED		Distance from Light Source					
Mounting Height	0'	1'	2'	3'	4'		
foot candles at 12"	56.90	13.60	2.02	1.02	0.61		
foot candles at 24"	16.70	8.28	3.80	0.91	0.56		
foot candles at 36"	7.50	4.40	2.80	1.56	0.54		



9 LED		Distance from Light Source					
Mounting Height	0'	1'	2'	3'	4'		
foot candles at 12"	79.40	21.90	2.81	1.40	0.82		
foot candles at 24"	24.00	12.16	5.00	1.42	0.94		
foot candles at 36"	11.64	7.32	4.48	2.87	1.10		

ORDERING INFORMATION

EXAMPLE: 15745AZT (Product # & Finish)

PRODUCT	WATTAGE/STYLE	FINISHES	OPTIONAL
3-LED Fixture 15745	.75 Watts / 1.3 Voltage Amps 	AZT - Architectural Textured Bronze (Shown Above) BBR - Bronzed Brass 	
6-LED Fixture 15746	1.4 Watts / 2.4 Voltage Amps 	CO - Copper (Will Naturally Patina Over Time) 	
9-LED Fixture 15756	2.2 Watts / 3.7 Voltage Amps (Shown Above) <u>Please Note:</u> Not For Use With Electronic Transformers	GRY - Gray  SD - Sand  WHT - Textured White 	

NOTES

**Definition of 40,000 hours: Voluntarily following the accepted industry standard of L70, Kichler rates the entire lighting fixture system at 40,000 hours; with engineered electronics that will last at least 40,000 hours, superior optical engineering, and finally utilizing a design that operates at the optimal temperature thresholds for the LED chips. The end result is a complete light fixture that does not require replacement parts and will provide 70% or more of its original light output for at least 40,000 hours. It has been proven that the human eye can hardly detect any difference in light output when light output is at 70% or above of its original output.



For Warranty Information,
please visit www.landscapelighting.com

We reserve the right to revise the design or components of any product due to parts availability or change in UL standards, without assuming any obligation or liability to modify any products previously manufactured, and without notice.