

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:

DESCRIPTION

naturaLED® Recessed Downlight Retrofits offer you an LED lighting solution to replace 60W to 120W incandescent recessed lamp types. Designed as an energy-efficient lighting solution for the industry's most popular 4, 5, 6 inch recessed downlight fixtures. Easy installation with Wet Location certified, our retrofit recessed downlights are dimmable, CRI 90 rated, and E26 adapter included. Available RL in 3000K or multiple temperatures which can easily select: 2700K, 3000K, 3500K, 4000K, or 5000K.

APPLICATIONS

Bathroom, Over Mirror, Accent, Residential, Hospitalities



Rated Life 35,000/50,000 Hrs
Warranty 3 / 5 Years

FEATURES


- Energy Star
- IC Rated
- Wet Location
- Air-Tight Certified
- ETL Listed
- Color Temp Selectable: 3000K/ CCT5 (27K/30K/35K/40K/50K)
- Voltage: 120V
- CRI: 90
- Powerfactor >0.9
- Surge Protection:
3000K = 2.5KV
CCT5 = 1.5KV
- TRIAC/ Incandescent dimming
- Beam Angle: Flood
- Operating temperature: 5°F - 104°F
- 3 Year Warranty, 35,000 hrs (for Single CCT)
- 5 Year Warranty, 50,000 (for CCT5)
- Finish: White

ACCESSORIES



Trims (Black, Bronze, White, Chrome) *

*Available for CCT5 models only



CCT SELECTABLE

5 color temperatures with selector switch

CCT: (2700K, 3000K, 3500K, 4000K, 5000K)

SAMPLE NUMBER LED6RL14-110L9CCT5

STYLE	DIAMETER	SERIES	WATTAGE	LUMEN	CRI	COLOR TEMP
LED led lighting	6 5/6 inch	RL commercial recessed light	14 14 watt	110L 1,100 Lumens	9 CRI90	CCT5 selectable color temperature 2700K, 3000K, 3500K, 4000K, 5000K



ORDERING

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Size	Warranty (yrs)	Wet Location	Energy Star
9	9524	LED4RL9-55L930	3000K	550	60	4"	3	•	•
14	9525	LED6RL14-110L930	3000K	1,100	120	5/6"	3	•	•
10	9526	LED4RL10-75L9CCT5	27K / 30K / 35K / 40K / 50K	750	80	4"	5	•	•
14	9527	LED6RL14-110L9CCT5	27K / 30K / 35K / 40K / 50K	1,100	120	5/6"	5	•	•

ACCESSORIES (Ordered Separately) *Fits CCT5 Version only

Trim- Black
P10170 RT-4RL9-BK
(Round Trim in Black for #9526)

Trim- Chrome
P10171 RT-4RL9-CH
(Round Trim in Chrome for #9526)

Trim- White/ Chrome
P10172 RT-4RL9-CH-WH
(Round Trim in White/Chrome for #9526)

Trim- White
P10176 RTS-4RL9-WH
(Square Trim in White for #9526)

Trim- Black
P10173 RT-6RL15-BK
(Round Trim in Black for #9527)

Trim- Chrome
P10174 RT-6RL15-CH
(Round Trim in Chrome for #9527)

Trim- White/ Chrome
P10175 RT-6RL15-CH-WH
(Round Trim in White/Chrome for #9527)

Trim- White
P10177 RTS-6RL15-WH
(Square Trim in White for #9527)


Trim- Bronze
P10404 RT-6RL15-BZ
(Round Trim in Bronze for #9527)

Base
P10029 ADP-RLGU24-N
(GU24 Socket Adaptor)


4" Trim for CCT5 Version

5/6" Trim for CCT5 Version

DIMENSIONS



PHOTOMETRICS CHART



PACKAGE

