

Version	2.0	Date	7/22/21
Prepared By	C.L.		

PRODUCT SPECIFICATION			
Category	Troffer		
Item Number	9595		
Stock Code	FXTF36SW/2X2/8CCT3/347		
Mounting	Ceiling		
Housing Color	White		

PICTURE



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	36 / 30 / 20	Replacement Wattage (W)	60 ~ 100
Tested Wattage (W)	36		
Input Voltage (V)	120 ~ 347		
Voltage Frequency (Hz)	50/60	Surge Protect Level	2KV
Input Current (A)	max 0.34	Dimmable	0-10V
Power Factor	>0.9	AUX (12V) Line	No
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	4572/3900/2640	CCT (K)	3500
Lumen (lm)	4896 / 4140/2800	CCT (K)	4000
Lumen (lm)	4680/ 3960/2680	CCT (K)	5000
Efficacy (lm/w)	>127	Beam Angle (°)	115
CRI	80		


GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-4 ~ 104
Storage Temperature (°F)	-4 ~ 140
IP Rating	UL Damp Location
Rated Life	50000 hrs.
Warranty	5 Years

ACCESSORIES		
Item #	Stock Code	Description
K7334225	FXTF-BAEM-MT	Emergency Driver Kit (7334 + P10225)
P10438	SEN-HB001VCR-1	12V Motion Sensor 0-10V
P10228	MT-2X2FMBOX	Flange Mount Kit
P10147	MT-ACC-4FT	Air Craft Cable - 4ft
*See Page 2 for more accessories		

PRODUCT DIMENSIONS			
Width- in (mm)	23.74" (603 mm)		
Height- in (mm)	1.97" (50 mm)		
Depth- in (mm)	23.74" (603 mm)		
EPA (ft²)	N/A		
Weight (lbs)	8		
Mounting Height (ft)	10		
Cable Length (ft)	-		

CERTIFICATIONS			
UL/ETL	ETL/ cETL	CEC	
NSF / ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	V5.1 Standard	RoHs	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	



COMMENTS	