

DESCRIPTION

naturaLED® PAR LED bulb provides a superior replacement for all incandescent lamp applications. An energy efficient integrated LED driver deliver the same lumen output equivalent with up to 85% energy savings. Our LEDs are direct replacement with energy star certification.

Perfect for display case lighting, track lighting, jewelry lighting and general lighting.



FEATURES

- Energy Star Certified
- CEC / JA8-2016
- Direct replacement and Instant-On
- Up to 84% energy savings
- Contains no mercury or lead
- UL/cUL Listed
- Material: Polycarbonate
- Input Line Voltage: 120
- CRI: 90
- Dimmable
- Powerfactor >0.9
- Beam Angle: Flood
- Operating temperature: -4°F ~ 104°F
- Rated 25,000 hours average life

APPLICATIONS

- Display Case Lighting
- Recessed Downlight
- Accent Lighting
- General Lighting
- Residential Lighting
- Restaurant Lighting

WARRANTY

- 5 Year Warranty

Ordering Information

EXAMPLE: LED9BR30/65L/927

LED	9	BR30	65L	927
LED	Wattage 9 9-Watts	Style BR30 BR30	Lumens 65L 650 Lm	Color Temp/ CRI 9 CRI90 27 2700K


ORDERING

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Equiv. Wattage (W)	Base	CRI	Bulb Shape	Rated Hrs	Damp Location	Energy Star
8	5834	LED8R20/50L/927	2700K	525	50	E26	90	R20	25,000	•	•
8	5982	LED8R20/52L/950	5000K	525	50	E26	90	R20	25,000	•	•
9	5835	LED9BR30/65L/927	2700K	650	65	E26	90	BR30	25,000	•	•
9	5904	LED9BR30/81L/927	2700K	810	65	E26	90	BR30	25,000	•	•
9	5983	LED9BR30/71L/950	5000K	710	65	E26	90	BR30	25,000	•	•
12	5842	LED12BR30/90L/927	2700K	900	75	E26	90	BR30	25,000	•	•
12	5978	LED12BR30/90L/940	4000K	950	75	E26	90	BR30	25,000	•	•
12	5984	LED12BR30/95L/950	5000K	950	75	E26	90	BR30	25,000	•	•
11	5905	LED11BR40/100L/927	2700K	1,000	90	E26	90	BR40	25,000	•	•
15	5836	LED15BR40/120L/927	2700K	1,200	90	E26	90	BR40	25,000	•	•
15	5985	LED15BR40/130L/950	5000K	1,300	90	E26	90	BR40	25,000	•	•

SPECIFICATIONS


R20

Weight: 2.24-oz




BR30

Weight: 5.60-oz




BR40

Weight: 9.12-oz




PACKAGE

R20
BR30Package
(Master)

20

BR40

Package
(Master)

10